


		Class	Weight
1	Cover according to standard EN124 (☒)	A35 (3,5 t) ☐	13 kg
		B125 (12,5 t) ☐	45 kg
		C250 (25 t) ☐	55 kg
		D400 (40 t) ☐	90 kg
2	Maintenance shaft (☒)	800...1000 ☐	31 kg
		1000...1250 ☐	33 kg
		1250...1500 ☐	42 kg
		1500...1750 ☐	52 kg
		1750...2000 ☐	62 kg
		2000...2250 ☐	71 kg
		2250...2500 ☐	80 kg
3	Ladder		
4	Automatic closure		
5	Coalescing module		
6	Sludge trap	600 l	
7	Oil storage capacity	260 l	
8	Effective capacity	700 l	
9	Oil level alarm sensor (☒)	☐	
		Nominal flow rate	6 l/s
		Total capacity	1300 l
		Weight excluding manhole shaft/lid	200 kg

Product <b>NS</b>	Name <b>Oil/water separator SEPKO-6/600-T</b>	Scale <b>1:20</b>
Design by <b>V.Laucius</b>	Checked by <b>E.Mozuraitis</b>	Approved by <b>E.Kuodis</b>
 <b>UAB ENEKA</b> Vandziogalos g. 94 LT-47467 Kaunas, Lithuania tel. +37037377441, faks. +37037377907 www.eneka.lt, info@eneka.lt		Construction site - Drawing type <b>Customer drawing</b> Drawing no. - Date <b>6/21/2019</b> Lang. <b>en</b> Sheet <b>1</b>