



1	Cover according to standard EN124 (☒)	Class	Weight
		A35 (3,5 t) ☐	13 kg
2	Maintenance shaft (☒)	B125 (12,5 t) ☐	45 kg
		C250 (25 t) ☐	55 kg
		D400 (40 t) ☐	90 kg
		800...1000 ☐	31 kg
		1000...1250 ☐	33 kg
		1250...1500 ☐	42 kg
		1500...1750 ☐	52 kg
3	Ladder	1750...2000 ☐	62 kg
		2000...2250 ☐	71 kg
4	Automatic closure	2250...2500 ☐	80 kg
5	Coalescing modules		
6	Sludge trap	600	
7	Oil storage capacity	180 l	
8	Effective capacity	910 l	
9	Oil level alarm sensor (☒)	☐	
Nominal flow rate		3 l/s	
Total capacity		1600 l	
Weight excluding manhole shaft/lid		185 kg	

Product NS	Name Oil/water separator SEPKO 3/600	Scale 1:50
Design by M.Skužinskas	Checked by E.Mozūraitis	Approved by E.Kuodis
 UAB ENEKA Vandziogalos g. 94 LT-47467 Kaunas, Lithuania tel. +37037377441, faks. +37037377907 www.eneka.lt, info@eneka.lt		Drawing type Customer drawing Drawing no. NS3-600-V-13-01BS Date 2015.09.07 Lang. en Sheet 1